


TO系列 泛用型

TO Series E Type



框架容量 (AF)		50		50		100		100		125	
型式		TO—50E		TO—50EC		TO—100EC		TO—100EB		TO—125EC	
極數		2		3		3		2 3		2 3	
額定電流(A) 基準周圍溫度40℃		15 40 20 50 30	15 40 20 50 30	15 40 75 20 50 100 30 60				15 40 75 20 50 100 30 60 125			
額定電壓 (V)		CNS,IEC 690									
額定啟斷容量 (kA)											
CNS 2931 JIS C8370 非對稱值/對稱值 Asym/sym	AC 550V 600V	1.5/1.5		5/5		7.5/7.5		10/10			
	AC 440V 480V	2.5/2.5		7.5/7.5		12/10		18/15			
	AC 380V	2.5/2.5		10/10		18/15		25/22			
	AC 220V 240V	5/5		18/15		30/25		35/30			
CNS 14816-2 IEC 60947-2 EN 60947-2 Icu/Ics	AC 500V	1.5/0.8		5/2.5		7.5/3.8		10/5			
	AC 440V	2.5/1.3		7.5/3.8		10/5		15/7.5			
	AC 415V	2.5/1.3		7.5/3.8		10/5		15/7.5			
	AC 380V	2.5/1.3		10/5		15/7.5		22/11			
	AC 230V	5/2.5		15/7.5		25/13		30/15			
DC	250V	2.5		5		7.5		10			
	125V	5		7.5		15		15			
外型尺寸 (mm) 	a	50		75		75		50 75		60 90	
	b	130		130		130		155			
	c	60		68		68		68			
	ca	79		87		87		86			
	aa	—		25		25		— 25		— 30	
	bb	111		111		111		132			
	重量 (kg)	0.4		0.6		0.8		0.62 0.8		0.7 1.0	
標準功能及特點											
過載跳脫方式		熱動—電磁									
跳脫按鈕		●									
ON/OFF指示器		—									
把手安全裝置		—									
接線方式		壓著端子									
可加裝之附屬裝置											
內部配件	電壓跳脫裝置	SHT	●③	●③	●③	●③	●				
	欠電壓跳脫裝置	UVT	●③	●③	●③	●③	—				
	輔助開關	AUX	●③	●③	●③	●③	●				
	警報開關	ALT	●③	●③	●③	●③	●				
	輔助+警報開關	AUX+ALT	●③	●③	●③	●③	●				
外部配件	電動操作機構	CD	—	●④	●④	— ●④	— ●④				
	外部 操作 把手	FH	—	●	●	— ●	— —				
		FL	—	—	—	— —	— ●				
		FG	—	●②	●②	— ●②	— ●②				
		TFJ	—	—	—	—	—				
	輔助把手	EHA	—	—	—	—	—				
	端子板	TBB	—	—	—	—	—				
	端子隔離板	TQQ	●	●	●①	●①	●①				
	端子保護蓋	XPR	—	●	●	— ●	— ●				

註：●：適用 —：不適用 ①：標準附件 ②：FG符合IP-42防塵、防水等級。
 ③：可單獨出售。 ④：非標準品，屬期貨需提前下訂。