



MOLDED CASE CIRCUIT BREAKER


無熔線斷路器

電子式系列 | 過負載 / 短路 保護兼用

工廠驗證



產品規格表

框 架 容 量 (AF)			1600			
型 式			NF1600-E			
額定電流In (A)(AT) 基準周圍溫度40°C			800	1000	1200	1600
極 數 (P)			可調整 0.5In~1.0In			
額定絕緣電壓 Ui (V)			可調整 0.4In~1.0In			
額定工作電壓 Ue (V)			3			
外型 及 安 裝 尺 寸			690			
			—			
			600			
			210			
			406			
			140			
製 品 重 量 (kg)			190			
額 定 啟 斷 容 量 (kA)	CNS 14816-2 IEC 60947-2 EN 60947-2 JIS C8201-2 Icu/Ics AC	*550V *600V	375			
		440V *480V	70			
		380V *415V	23			
		220V *240V	30.5			
	NEMA asym/sym AC	*550V *600V	65/33			
		440V *480V	85/43			
		380V *415V	100/50			
		220V *240V	130/65			
接 線 方 式			銅接板			
選 購 配 件	警 報 接 點 (AL)		—			
	輔 助 開 關 (AX)		—			
	低電壓跳脫裝置 (SHT)		—			
	外部操作把手		—			
	端 子 隔 離 蓋		—			
過載跳脫方式			電子式			
跳 脫 按 鈕			有			